



Product Data

BioBar Range

Environmentally Acceptable Lubricant for hydraulics

Description

Castrol BioBar is a range of environmentally acceptable hydraulic fluids which can replace conventional mineral oils in hydraulic equipment where leakage or spillage may result in escape into the marine environment.

Castrol BioBar hydraulic fluids are formulated from synthetic ester base oils which are selected to give a wide operating temperature range and long service life.

Extensive testing of Castrol BioBar and hydraulic system components (in particular, elastomer seals) has confirmed good compatibility with standard components, which can allow conversion of existing equipment without the need for major changes.

Castrol BioBar hydraulic fluids have been tested and registered according to OSPAR (Oslo and Paris Convention for the Protection of the Marine Environment of the North-East Atlantic) requirements and therefore complies with current 2018 US Vessel Incidental Discharge Act (VIDA) criteria for Environmentally Acceptable Lubricants (EALs) as it meets the definition of an Environmentally Acceptable Lubricant (EAL) under the US Vessel General Permit (VGP) 2013.

Application

Hydraulic systems are extensively used for power transmission on board ship. Cranes, winches, windlasses and life boat davits are often located where leakage or spillage can escape into the marine environment. The extensive use of flexible hoses, which are susceptible to mechanical damage through abrasion or fatigue, can increase the risk of leakage which can lead to a rapid loss of fluid if there are high operating pressures and high flow rates.

Castrol BioBar is recommended for hydraulic systems and hydrostatic transmissions which incorporate gear pumps, vane pumps, radial piston or axial piston pumps and motors and where there is a perceived risk of egress into the environment in the event of spillage or leakage.

Advantages

Reduced environmental impact when compared to conventional lubricants – demonstrable benefits in the following key environmental performance criteria:

- Superior biodegradation
- Significantly reduced bioaccumulation* and toxicity
- Enhanced renewability

(*) Using OSPAR criteria for assessing bioaccumulation potential.

High levels of protection given to pump and motor components, which can contribute to a high level of reliability:

- Minimal wear of ring and vane in Vickers PM 104C pump test
- Minimal wear of ring and vane in Eaton-Vickers 35VQ25 pump test

Typical Characteristics

Name	Method	Units	BioBar 22	BioBar 32	BioBar 46	BioBar 68
Kinematic Viscosity @ 40°C / 104°F	ISO 3104, ASTM D445	mm ² /s	22	32	46	68
Kinematic Viscosity @ 100°C / 212°F	ISO 3104, ASTM D445	mm ² /s	4.9	6.4	8.2	11.0
Viscosity Index	ISO 2909, ASTM D2270	None	139	145	147	150
Density @ 15°C / 59°F	ISO 12185, ASTM D4052	kg/m ³	900	900	920	950
Pour Point	ISO 3016, ASTM D97	°C (°F)	-42 (-43)	-42 (-43)	-36 (-33)	-36 (-33)
Flash Point, open cup method	ISO 2592, ASTM D92	°C (°F)	226 (438)	232 (449)	218 (424)	230 (446)
Rust test, synthetic seawater (24 hours)	ISO 7120, ASTM D665B	rating	Pass	Pass	Pass	Pass
Copper corrosion, 3 hours @ 100°C / 212°F	ISO 2160, ASTM D130	rating	1A	1A	1A	1A
Foam Sequence I, tendency / stability	ISO 6247, ASTM D892	ml/ml	20/0	20/0	20/0	20/0
Oxidation Stability - Rotating Pressure Vessel test	ASTM D2272	minutes	300	300	300	315

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Additional Information

Castrol BioBar hydraulic fluids are fully miscible with conventional mineral oils and compatibility has been confirmed by testing with several standard grades. However, Castrol strongly recommends that the guidelines given for changeover in ISO 15380: 2002 Annexe 1 are followed closely and that the residual mineral oil in the system is reduced to 2%. This is to ensure that the intended environmental performance is achieved, as well as to ensure reliable operation. This figure can usually be achieved without flushing being required. A significant proportion of the fluid volume in a hydraulic system is contained in pipework, actuators and accumulators and this needs to be expelled back to the reservoir and removed during changeover.

There are many different types of hydraulic fluids which are marketed as biodegradable or environmentally friendly, which are based upon a variety of different base oil types. As a general rule Castrol does not recommend mixing different types of hydraulic fluids due to the number of different base oils and additive system combinations which are possible. There are exceptions but compatibility testing is required before confirmation can be given.

Castrol BioBar does not require any additional maintenance in service over and above that which is considered good practice for hydraulic fluids in general service. Water removal equipment and additional filtration will prolong the life of system components and of the lubricant, and is recommended. Some Class Societies may insist on the installation of water removal equipment whenever EALs are used.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BioBar Range

30 Jul 2025

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine