

Cyltech 70f

Section 1. Identification

Product name Cyltech 70f
SDS # 471094
Code 471094-SG01

Relevant identified uses of the substance or mixture and uses advised against

Product use Marine engine oil
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier Castrol BP Petco Limited Liability Company
Unit 20.01, level 20, The Nexus , 3A-3B Ton Duc Thang street, Sai Gon ward, Ho Chi Minh City, Vietnam
Tel: 84-28-38219596 / 38219153
Fax: 84-28-38219603 / 38219152
Carechem: +65 3158 1074 (24/7)

EMERGENCY SPILL INFORMATION:

Section 2. Hazards identification

Classification of the substance or mixture REPRODUCTIVE TOXICITY - Category 1B

GHS label elements

Hazard pictograms



Signal word Danger
Hazard statements H360 - May damage fertility or the unborn child.

Precautionary statements

Prevention P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing and eye or face protection.
Response P308 + P313 - IF exposed or concerned: Get medical attention.
Storage P405 - Store locked up.
Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Other hazards which do not result in classification Defatting to the skin.
USED ENGINE OILS
Used engine oil may contain hazardous components which have the potential to cause skin cancer.
See Toxicological Information, section 11 of this Safety Data Sheet.

Section 2. Hazards identification

Defatting to the skin.

USED ENGINE OILS

Used engine oil may contain hazardous components which have the potential to cause skin cancer.

See Toxicological Information, section 11 of this Safety Data Sheet.

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic	CAS: 64742-54-7	≥50 - ≤75
Residual oils (petroleum), hydrotreated	CAS: 64742-57-0	≤10
Residual oils (petroleum), solvent-dewaxed	CAS: 64742-62-7	≤10
Paraffin oils (petroleum), catalytic dewaxed heavy	CAS: 64742-70-7	≤5
Distillates (petroleum), hydrotreated light paraffinic	CAS: 64742-55-8	≤5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS: 64742-65-0	≤5
Phenol, dodecyl-, sulphurised, carbonates, calcium salts, overbased	CAS: 68784-26-9	≤3
Alkyl phenol	CAS: 74499-35-7	≤0.3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Inhalation

If inhaled, remove to fresh air. Get medical attention.

Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention. If skin irritation or rash occurs: Get medical attention.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

Specific treatments

No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media Do not use water jet.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Section 7. Handling and storage

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	Ministry of Health (Viet Nam) [mineral oil] TWA 8 hours: 5 mg/m ³ . Form: Mist. Issued/Revised: 10/2002. STEL 15 minutes: 10 mg/m ³ . Form: Mist. Issued/Revised: 10/2002.
Residual oils (petroleum), hydrotreated	Ministry of Health (Viet Nam) [mineral oil] TWA 8 hours: 5 mg/m ³ . Form: Mist. Issued/Revised: 10/2002. STEL 15 minutes: 10 mg/m ³ . Form: Mist. Issued/Revised: 10/2002.
Residual oils (petroleum), solvent-dewaxed	Ministry of Health (Viet Nam) [mineral oil] TWA 8 hours: 5 mg/m ³ . Form: Mist. Issued/Revised: 10/2002. STEL 15 minutes: 10 mg/m ³ . Form: Mist. Issued/Revised: 10/2002.
Paraffin oils (petroleum), catalytic dewaxed heavy	Ministry of Health (Viet Nam) [mineral oil] TWA 8 hours: 5 mg/m ³ . Form: Mist. Issued/Revised: 10/2002. STEL 15 minutes: 10 mg/m ³ . Form: Mist. Issued/Revised: 10/2002.
Distillates (petroleum), hydrotreated light paraffinic	Ministry of Health (Viet Nam) [mineral oil] TWA 8 hours: 5 mg/m ³ . Form: Mist. Issued/Revised: 10/2002. STEL 15 minutes: 10 mg/m ³ . Form: Mist. Issued/Revised: 10/2002.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ministry of Health (Viet Nam) [mineral oil] TWA 8 hours: 5 mg/m ³ . Form: Mist. Issued/

Product name Cyltech 70f

Product code 471094-SG01

Page: 4/14

Date of issue 02/15/2026.

Format Vietnam

Language ENGLISH

Version 2

(Vietnam)

(ENGLISH)

Section 8. Exposure controls/personal protection

Revised: 10/2002.

STEL 15 minutes: 10 mg/m³. Form: Mist.
Issued/Revised: 10/2002.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Colour

Amber. [Dark]

Odour

Not available.

Odour threshold

Not available.

pH

Not applicable.

Melting point/freezing point

Not available.

Boiling point or initial boiling point and boiling range

Not available.

Flash point

Closed cup: 249°C (480.2°F) [Pensky-Martens ASTM D 93]

Evaporation rate

Not available.

Flammability

Not available.

Lower and upper explosion limit/flammability limit

Not available.

Vapour pressure

Ingredient name	Vapour Pressure at 20 °C			Vapour pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.07501	<0.01	ASTM D 5191			
Residual oils (petroleum), solvent-dewaxed	<0.07501	<0.01	ASTM D 5191			
Paraffin oils (petroleum), catalytic dewaxed heavy	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191			

Relative vapour density

Not available.

Density

<1000 kg/m³ (<1 g/cm³) at 15°C

Relative density

Not available.

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-octanol/water

Not applicable.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Product name Cyltech 70f

Product code 471094-SG01

Page: 6/14

Date of issue 02/15/2026.

Format Vietnam

Language ENGLISH

Version 2

(Vietnam)

(ENGLISH)

Section 9. Physical and chemical properties

Viscosity Kinematic: 202.1 mm²/s (202.1 cSt) at 40°C
Kinematic: 19 to 21 mm²/s (19 to 21 cSt) at 100°C

Particle characteristics

Median particle size Not applicable.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours]
OECD 403

Distillates (petroleum), hydrotreated light paraffinic

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours]
OECD 403

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Rat - Dermal - LD50

>2000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours]
OECD 403

Product name Cyltech 70f

Product code 471094-SG01

Page: 7/14

Date of issue 02/15/2026.

Format Vietnam

Language ENGLISH

Version 2

(Vietnam)

(ENGLISH)

Section 11. Toxicological information

Skin corrosion/irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result

Rabbit - Skin - Mild irritant

OECD 404

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.

Serious eye damage/eye irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result

Guinea pig - skin

OECD 406

Result: Not sensitising

Guinea pig - skin

OECD 406

Result: Not sensitising

Guinea pig - skin

OECD 406

Result: Not sensitising

Germ cell mutagenicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light

Result

In vitro - Bacteria

Bacterial Reverse Mutation Test

Result: Negative

In vitro - Mammal - species unspecified

In vitro Mammalian Chromosomal Aberration Test

Result: Negative

In vivo - Mammal - species unspecified

Mammalian Erythrocyte Micronucleus Test

Result: Negative

In vitro - Mammal - species unspecified

In vitro Mammalian Cell Gene Mutation Test

Result: Negative

In vitro - Bacteria

Product name Cyltech 70f

Date of issue 02/15/2026.

Version 2

Product code 471094-SG01

Format Vietnam

(Vietnam)

Page: 8/14

Language ENGLISH

(ENGLISH)

Section 11. Toxicological information

paraffinic

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Carcinogenicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy
paraffinic

Result

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Reproductive toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy
paraffinic

Result

Rat - Oral

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Rat - Oral

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Distillates (petroleum), hydrotreated light
paraffinic

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Rat - Oral

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Product name Cyltech 70f

Product code 471094-SG01

Page: 9/14

Date of issue 02/15/2026.

Format Vietnam

Language ENGLISH

Version 2

(Vietnam)

(ENGLISH)

Section 11. Toxicological information

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Potential chronic health effects

Not available.

General

USED ENGINE OILS
Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 11. Toxicological information

Section 12. Ecological information

Toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Section 12. Ecological information

OECD 201
Algae
≥100 mg/l [72 hours]
Chronic - NOEL
OECD 211
Daphnia
10 mg/l [21 days]

Environmental effects No known significant effects or critical hazards.

Persistence and degradability

Expected to be biodegradable.

Product/ingredient name

Result

Distillates (petroleum), hydrotreated heavy paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), hydrotreated light paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed heavy paraffinic

OECD 301F
31% [28 days] - Not readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Phenol, dodecyl-, sulphurised, carbonates, calcium salts, overbased	9.5	-	High
Alkyl phenol	6.1	-	High

Mobility in soil

Soil/water partition coefficient

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

International lists

Australia inventory (AIC)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

At least one component is not listed.

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Japan inventory (CSCL)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

At least one component is not listed.

Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

United States inventory (TSCA 8b)

All components are active or exempted.

Section 16. Other information

History

Date of issue/ Date of revision 15 February 2026
Date of previous issue 2/12/2026
Prepared by Product Stewardship

Product name Cyltech 70f

Product code 471094-SG01

Page: 13/14

Date of issue 02/15/2026.

Format Vietnam

Language ENGLISH

Version 2

(Vietnam)

(ENGLISH)

Section 16. Other information

Key to abbreviations

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.